

WHEN IT COMES TO AIRTIGHTNESS, WE HAVE YOUR NEW BUILD OR RENOVATION PROJECT COVERED



USE INDOORS & OUTDOORS

Airstop Adhesive Tape

DESCRIPTION

Airstop Adhesive Tape is a tear-resistant tape with adhesive generously applied and is suitable for a variety of bonding applications, indoors and out. It is a semi-rigid tape suitable for applying to straight joints, along substrates such as plywood, OSB and membranes. Its reinforced make-up makes it resistant to tearing. If you require the tape to be plastered or painted over, then please use our Airstop Flex Tape.

BENEFITS/USAGE

- Adhesion of vapour retarders & airtight layers
- Joints of OSB & DWD (wood fibre board) panels, indoors & outdoors
- Joints & connections with wood, OSB, metal
- For adhesion to masonry use a primer if necessary
- Joint connections to the higher standards of ÖNORM B 5320 & DIN 4108-7 are possible
- 30 year resistance to ageing

PREPARATION

Any surface being adhered to should be properly prepared and must be free from dust and grease and substrates must be dry. For porous substrates such as XPS, concrete, masonry, etc., please use Bubi LF Bonding Primer where necessary. The greater the pressure applied, the better the performance of the adhesive tape.

APPLICATION

Apply off the roll or cut to desired length. Press firmly into position. For further information see our application guidelines.

NOTE

Airstop Adhesive Tape functions as a seal and not as a mechanical fixing. The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is extremely resistant to ageing. Please pay attention to our Guidelines for Installation!



Composition	Tear-resistant system adhesive tape with pure acrylate adhesive						
Roll Widths mm	50	60	80	10	0 15	0 17	0 200
Roll Length m	50	50	50	50	50	50	50
Rolls/Carton	8	8	4	4	2	2	2
Thickness	Approx. 0.3mm						
Temperature Resistance	-40°C to +100°C						
Working temperature	From -5°C						
Resistance to Ageing	30 years						
Storage	2 years, cool and dry						
UV-Resistance	Max. 2 months						
Colour	White with Airstop imprint						









